ACROLINK®

7N Cu SPEAKER CABLE
Stressfree® 99.99999% Purity Copper

7N-S1000 Leggenda



SPECIFICATIONS

Outer diameter	: 7.7×19mm
Signal Conductor	: 7N D.U.C.C Stressfree 0.37φ×18 Strands (2 cores)
Single Conductor size	: 1.93 Sq (AWG 14)
Insulation material	: High molecular Polyolefin Resin (Red & White)
Resonance control core	: Conductive resonance control material (EMS absorbing non-magnetism thread inside)
Inner sleeve	: High molecular Polyolefin Resin
Shielding	: Copper tape
Outer sleeve	: Lead free Polyvinyl Chloride (Pearl white finish)
Conductor resistance	: 7.5mΩ/m
Electrostatic capacitance	: 11pF/m

●Packaging: 30m on spool



7N-S1400 Leggenda



SPECIFICATIONS

Outer diameter	: 9.5×20.5mm
Signal Conductor	: 7N D.U.C.C Stressfree 0.37φ×50 Strands (2 cores)
Single Conductor size	: 5.36 Sq (AWG 10)
Insulation material	: High molecular Polyolefin Resin (Red & White)
Resonance control core	: Conductive resonance control material (EMS absorbing non-magnetism thread inside)
Inner sleeve	: High molecular Polyolefin Resin
Shielding	: Copper tape
Outer sleeve	: Lead free Polyvinyl Chloride (Pearl white finish)
Conductor resistance	: 2.7mΩ/m
Electrostatic capacitance	: 19pF/m

●Packaging: 30m on spool